

聚氯乙烯树脂规格表 PVC RESIN SPECIFICATION

产 品 型 号 PRODUCT TYPE		DG-700	DG-800T	DG-1000S	DG-1300
PHYSICAL/CHEMICAL PROPERTY 理 化 特 征		White powder 白 色 粉 末			
技术规格 TECHNICAL SPECIFICATION	Average polymerization degree: 平均聚合度:	700+/-50	800+/-50	1030+/-50	1300+/-80
	Impurity particle number/100g 杂质粒子数, 个/100g ≤	50max	50 max	50 max	50 max
	Volatile matter 挥发物 ≤	0.3%max	0.3% max	0.3% max	0.3% max
	Bulk density g/ml: 表面密度 g/ml:	0.57+/-0.04	0.54+/-0.03	0.53+/-0.03	0.50+/-0.04
	0.35mm Particle size 0.35mm 筛余物 ≤	0.1% max	0.1% max	0.1% max	0.1% max
	Initial whiteness 原始白度 ≥	90% min	90% min	90% min	90% min
	Whiteness (160℃, 10min) 白度 (160℃, 10min) ≥	75% min	78% min	78% min	78% min
	VCM residuals ug/g VCM 残留 ug/g ≤	1 max	1 max	1 max	1 max
	Fish eyes number/100cm2 鱼眼数 个/100cm2 ≤	12 max	6 max	5 max	5 max
K Value: K 值:		55-59	60 - 62	66 - 68	71-72
包 装 PACKAGE	Packing in 25kg net pp/kraft paper bags or 600kg/1200kg jumbo bags. 25千克复合牛皮纸袋或600千克/1200千克大包装袋				Packing in 25kg pp/kraft paper bags or 500kg/1000kg jumbo bags. 25千克复合牛皮纸袋或500千克/1000千克大包装袋
主要用途 MAIN USAGE	Used to manufacture various kinds of plates, sheets, pipe fittings etc. 用于生产各种板材、片材、管件等	Used to manufacture bottles, transparent sheets, sheets, pipe fittings etc. 用于生产瓶子、透明片、片材、管件等	Used to manufacture various kinds of PVC profiles, piping materials etc. 用于生产各种 PVC 型材、管材等	Used to manufacture electrical insulating materials, thin films, artificial leather surface film etc. 用于生产电绝缘材料、薄膜、人造革表面膜等	



Mob : + 91 8910506413 / 9831235030

<https://www.interchemindia.in>